



NORUSTO STANDARD BLACK

BITUMINOUS PAINT AND WATERPROOF COATING

FEATURES

- § Can be applied to a wide variety of substrates
- § Waterproof qualities
- § Can withstand adverse climates
- § For use on:
 - Metal
 - Asphalt and roofing felts
 - Masonry and other surfaces
- § Supplied ready for use

Applied at:

Metal surfaces: 10-12m² per litre per coat
Masonry surfaces: 5-6m² per litre per coat

Complies with: BS6949; 1988, Type 1, Class A

DESCRIPTION

NORUSTO bituminous paint and water proofing is a black bituminous solution in white spirit. It retains its waterproofing qualities under all climatic conditions and is little affected by acid fumes, salt water, sea air or alkalinity. On exposure to normal weathering it will lose its initial gloss and is not intended for decorative finishes.

NORUSTO STANDARD BLACK is a general purpose inexpensive bituminous solution for application to a wide variety of metal surfaces such as zinc or lead roofs and for rain water gutter interiors and down pipes. Forms a waterproof bond over render, cement, brick, stone, concrete, wood or metal. Suitable as a top dressing for asphalt surface and for renovating bitumen roof felt. (NORUSTO STANDARD BLACK is unsuitable for use in contact with drinking water.)

PACKAGING

STANDARD BLACK is supplied in 5 and 25 litre packs.

INSTRUCTIONS FOR USE

Preparation: Both for initial application and redecoration, all surfaces must be thoroughly dry, clean and free from rust, grease, oil, dirt and other loose material before painting.

Application: Avoid painting in unsuitable conditions e.g. damp, foggy or misty weather, or when the surface is frosted or wet, or below 5°C. Generally, coatings should not be applied if the ambient temperature is below 5°C or relative humidity exceeds 80%.

NOTE: the temperature of heavy metal sections or plates as well as plaster, rendering and masonry can be several degrees below the ambient, especially early in the day.

Observe the recommendations of BS6150: 1982 Code of Practice for Painting of Buildings.

Stir the NORUSTO thoroughly before use. Apply by brush, cold, without dilution. For spray application a maximum of 5% white spirit by volume may be added to STANDARD BLACK.

Two coats of STANDARD BLACK are recommended, especially on badly pitted surfaces. Under conditions of free ventilation and warm, dry atmosphere NORUSTO will be touch dry in 4 hours and once fully dry (normally 24-48 hours) may be recoated. When redecorating existing NORUSTO finishes, apply one or two coats as necessary.

Cleaning: After use, brushes and equipment should be cleaned with white spirit.

PROPERTIES

Flash point: 40°C.
Density (g/cm³): 0.89 - 0.94
Drying time: In good conditions, touch dry in 4 hours, recoatable in 24-48 hours.



COMPATIBILITY

NORUSTO bituminous paint should not be mixed with, or applied over oil or gloss paints, or be overpainted.

SAFETY INFORMATION

Dangerous for the environment.

Harmful.

Flammable.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Keep away from sources of ignition - No smoking.

Avoid contact with skin.

Wear suitable protective clothing, gloves and eye / face protection.

Avoid release to the environment. Refer to safety data sheets.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

PRECAUTIONS

The handling and safety precautions shown on the product label must be understood and followed at all times. In general terms, care must be taken to avoid contact with eyes and skin, oral ingestion, and inhalation of vapour and fumes.

Flammable liquid: observe appropriate fire precautions.

Always consult the label and the Material Safety Data Sheet before use.

STORAGE

Avoid the formation or spread of mists in the air. Avoid direct contact with the substance. Store in cool, well ventilated area. Keep container tightly closed. This product should be stored in a secure place in its closed, original, labelled containers. Protect from extreme heat. Keep away from food, drink and animal foodstuffs.

ADDITIONAL INFORMATION

Osmoste provides a range of products and technologies for the treatment, protection and enhancement of timber. Information and advice is available on all aspects of our products from the Technical Services Department.

For more information visit www.osmoste-europe.com

Telephone: +44 (0) 1628 486644

Emergency : +44 (0) 1628 890907

*Osmoste and Celcure are registered trademarks of Protim Solignum Ltd. Protim Solignum Ltd trades as Osmoste. An Osmoste company.