

Léttull Rúllur

Compressable rolls. CE marked. Packed in transparent PE-foil.



Usage

Heat and sound insulation in roofs and floors, where the insulation will not be subjected to pressure or loads. Should not be used where temperature is above 200 °C.

Technical information

Nominal	Compressive Strength	Thickness Tolerances	Temp. Tolerances	Thermal Conductivity	Reaction to Fire	Short Term Water Absorption	CE - Marked
kg/m ³	kPa	Class	°C	W / mK	Euroclass	kg/m ²	Standard
22	NPD	T2	200	0,039	A1	≤1	
	IST EN 826	IST EN 823		IST EN 12939	IST EN 13501-1	IST EN 1609/12087	EN 13162

NPD - No Performance Determined

Size, Packing Specification and Thermal Resistance

Size			Pack		Pallet			Thermal Resistance
THICKNESS	WIDTH	LENGTH	SLABS	M ²	PACK	M ²	M ³	M ² K / W
* 50	570	10000	1	5,70	60	342,00	6,84	1,25
* 75	570	6800	1	3,88	60	232,56	6,82	1,90
* 100	570	5000	1	2,85	60	171,00	6,84	2,55
* 125	570	4000	1	2,28	60	136,80	6,84	3,20
* 150	570	3300	1	1,88	60	112,86	6,77	3,80

* Product is not in stock

Quality Control

The production at Sauðárkrókur follows a documented quality system verified according to ISO 9001 and environmental system according to ISO 14001.