

**DECLARATION OF PERFORMANCE Nr. LF-CPR/CE-DoP-03****1. Unique identification code of the product-type:**

Riga[®] birch plywood bonded with low emission urea-melamine-formaldehyde adhesive (interior gluing quality). Uncoated or overlaid.

2. Type, batch or serial number or any other element allowing identification of the construction product as required under CPR Article 11(4):

Riga[®] birch plywood bonded with low emission urea-melamine-formaldehyde adhesive (interior gluing quality). Uncoated or overlaid.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Non-structural components for internal use as in dry conditions (MR). EN 636-1

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant CPR Article 11(5):

Latvijas Finieris AS
Bauskas iela 59
Rīga
LV-1004 Latvia

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR Annex V:

AVCP System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Manufacturer had performed product type testing and has carried out continuous controls of factory production processes, laboratory tests and keeping of quality records according to the requirements stated by harmonised technical specification. Manufacturer's Quality Management system is certified to the EN ISO 9001 requirements by Bureau Veritas Certification.

Mill Lignums

Finiera iela 6
Rīga, Latvia, LV-1016

Mill Furniers

Bauskas iela 59
Rīga, Latvia, LV-1004

9. Declared performance

Harmonised technical specification EN 13986+A1:2015

Essential characteristics			PERFORMANCE											
			Sanded birch plywood											
			Nominal thickness, mm											
			4	6,5	9	12	15	18	21	24	27	30	35	
			Number of plies											
			3	5	7	9	11	13	15	17	19	21	25	
	Standard	Unit	lower 5% quantile 670, upper 5% quantile 760											
Density	EN323	kg/m ³	lower 5% quantile 670, upper 5% quantile 760											
Bending strength ^{1, 2}	EN310	F class EN636		50	50	40	40	40	40	35	35	35	35	35
			⊥	15	25	35	35	35	35	30	30	30	30	30
Bending stiffness ^{1, 2}	EN310	E class EN636		100	90	90	80	80	80	80	80	80	80	70
			⊥	10	30	40	50	60	60	60	60	60	60	60
Airborne sound insulation ³	EN13996+A1	dB	-	-	24,5	26,1	27,4	28,4	29,3	30,0	30,7	31,3	32,3	
Bonding quality	EN314	class	1 (interior)											
Release of formaldehyde	EN13986+A1 EN717-2	class	E1											
Reaction to fire	EN13986+A1 EN13501-1	class	End use condition	Minimum thickness, mm		Class (excluding floorings)		Class, floorings						
			without an air gap behind the panel	9		D-s2, d0		Dfl-s1						
			with a closed or an open air gap not more than 22mm behind the panel	9		D-s2, d2		-						
			with a closed air gap behind the panel	15		D-s2, d1		Dfl-s1						
			with an open air gap behind the panel	18		D-s2, d0		Dfl-s1						
			any	3		E		Efl						
Water vapour permeability	EN13986+A1	μ	Wet cup		90									
			Dry cup		220									
Sound absorption	EN13986+A1	coeffic.	Frequency range 250 Hz - 500 Hz				0,10							
			Frequency range 1000 Hz - 2000 Hz				0,30							
Thermal conductivity	EN13986+A1	W m ⁻³ K ⁻¹	0,17											
Biological durability	EN335	class	Uncoated or overlaid				Use class 1							
			Overlaid and with protected edges				Use class 2							

|| = parallel to the face grain
 ⊥ = perpendicular to the face grain

¹ Plywood moisture content 8± 2%

² Riga Ply classification according to EN 636


³ For calculation used average density 715 kg/m³

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

11. This information is presented for consumer as general information on technical specification and other characteristics of products manufactured by Latvijas Finieris AS mills Lignums and Furniers. Any other conditions (e.g., guaranties) shall be agreed separately, by signing respective agreement. Any claim for compensation is limited to the value of the defective panels.

12. The signed English version of this document is the official.

Signed for and on behalf of the manufacturer by:



Mārtiņš Lācis
Head of Marketing, Sales, Purchasing and Logistics

Riga, 30.11.2016